Applicant:

Heath, et al.

Filed: July 27, 1999

Title:

COMPUTER IMPLEMENTED NUCLEIC ACID

ISOLATION METHOD AND APPARATUS

AMENDMENT AND RESPONSE

Atty. Docket No.: 101.003US01

Serial No.:

Page 2 of 11

09/361.829

aspirating a sample;

mixing a sample;

dispensing into a sample;

controlling the temperature of a function;

removing material from a sample;

separating a sample; and

removing and separating a sample;

wherein each of the functions except centrifuging is performed external to a centrifuge.

6. A computer system for configuring a machine to automatically perform a method of isolating nucleic acids, the computer system comprising:

a computer;

a computer readable medium comprising machine readable instructions for causing the computer to output a command series to an automated nucleic acid isolation machine for control of the functions of nucleic acids isolation process;

wherein the computer readable medium comprises:

a software module comprising:

a centrifugation sub-module for issuing commands initiating centrifuging of a sample for a centrifuge time and a centrifuge speed;

an aspiration sub-module for issuing commands initiating aspirating a sample to remove a volume of fluid from a sample;

a mixing sub-module for issuing commands initiating mixing a sample;

a dispensing module for issuing commands initiating dispensing into a sample an amount of a specific reagent;

a temperature control module for issuing commands to control the temperature of a function;

a removal module for issuing commands to remove material from a sample;



'Applicant: Filed:

Heath, et al. July 27, 1999

Title:

COMPUTER IMPLEMENTED NUCLEIC ACID

ISOLATION METHOD AND APPARATUS

AMENDMENT AND RESPONSE

Page 3 of 11

09/361,829

Atty. Docket No.: 101.003US01

a separation module for issuing commands to separate a sample into components; and

a combination removal and separation module for issuing commands to control separating and removing a sample; and

wherein each sub-module except the centrifugation sub-module is configured to control operation external to a centrifuge.

Please cancel claim 7.



9. A control module for controlling the operation of an automated nucleic acids isolation apparatus, the module comprising:

a processor; and

a program module comprising a set of machine readable instructions for issuing commands to the automated nucleic acids isolation apparatus to perform a series of steps, comprising:

centrifuging a sample;

aspirating a sample;

mixing a sample;

adding a reagent to the sample;

controlling the temperature of an isolation function;

removing material from a sample;

separating a sample; and

separating and removing a sample;

wherein each of the functions except centrifuging is performed external to a centrifuge.



A computer control module for an automated nucleic acids isolation apparatus, the control module comprising:

 Applicant: Filed:

Heath, et al.

July 27, 1999

Title:

COMPUTER IMPLEMENTED NUCLEIC ACID

ISOLATION METHOD AND APPARATUS

AMENDMENT AND RESPONSE

Atty. Docket No.: 101.003US01

Page 4 of 11

a plurality of sub-modules, each sub-module comprising machine readable instructions for creating a command to the nucleic acids isolation apparatus to perform a process step of the nucleic acids isolation process; and an output link for communicating the commands to the nucleic acids isolation apparatus;

wherein the plurality of sub-modules comprises:

a centrifuge sub-module for issuing commands initiating centrifuging of a sample for a centrifuge time and a centrifuge speed;

an aspirate sub-module for issuing commands initiating aspirating a sample to remove a volume of fluid from a sample;

a mixing sub-module for issuing commands initiating mixing a sample; a dispensing module for issuing commands initiating dispensing into a sample an amount of a specific reagent;

a temperature control module for issuing commands to control the temperature of a function:

a removal module for issuing commands to remove material from a sample; a separation module for issuing commands to separate a sample into components; and a combination removal and separation module for issuing commands to control separating and removing a sample;

wherein each sub-module except the centrifugation sub-module is configured to control operation external to a centrifuge.

Please capeel claim 15.